

8 MAY 2017

ASSAYS CONFIRM HIGH-GRADE LITHIUM MINERALISATION IN MALLINA EAST PEGMATITE DISCOVERY

Highlights

- Rock chip assays up to 3.98% Li₂0 returned in new eastern spodumene pegmatite zone
- Results confirm lithium mineralisation in three new zones of spodumene pegmatites, with the main Eastern Pegmatite outcropping over 1,300 metres of strike extent
- Widths up to 20 metres observed on surface, true thickness unknown. Assays confirm lithium present as spodumene, which is observed all along the pegmatite body
- Exploration and permitting being fast-tracked to allow drill testing

Sayona Mining Limited (ASX: SYA) ("Sayona" or the "Company") is pleased to report the initial rock chip assay results from the new Mallina East spodumene pegmatite discovery in the Pilgangoora district of Western Australia.

The results confirm that the Mallina East pegmatite is mineralised along the 1.3 kilometre strike extent that has been identified and sampled to date. The highest lithium grades, up to 3.98% Li₂0, are hosted in a very coarse spodumene pegmatite. Of the 14 samples collected over the Eastern Pegmatite, the average lithium content is 1.23% Li₂O (see Figure 1 and Table 1). Some of this sampling however includes weathered silicified cap-rock, which although closely related to areas of spodumene mineralisation, is not itself mineralised. It is anticipated that spodumene is present in the fresh rock below these zones.

In addition to the Eastern Pegmatite, a number of other pegmatites have been identified, including a zone to the north-east of the main pegmatite which, assayed up to 3.16% Li₂O, and a western zone which assayed up to 0.52% Li₂O (see Figure 2). The new discovery areas remains very lightly explored and the initial results have confirmed the potential of the area.

The Mallina project, located in the world-class Pilgangoora lithium district of Western Australia, now includes seven areas containing spodumene pegmatite mineralisation (see Figures 2 and 5). Further exploration will continue around the discovery areas to define drill targets. Permitting and approvals are underway to allow drill testing of the targets as soon as possible.

Corey Nolan, Chief Executive Officer, commented "The Company is very encouraged by the potential scale of the new pegmatite which is demonstrating the potential for robust grade, thickness and strike extent. The Company will work towards drill testing the targets as quickly as possible".






Figure 1: Mallina East pegmatite initial rock chip results






Figure 2: Location of rock chip assays in eastern zone in close proximity to Mallina East



Figure 3: Zones of outcropping pegmatite in the new eastern zone





Figure 4: Spodumene mineralisation in the new Eastern Pegmatite




Figure 5: Location of the Company's projects including Mallina in the Pilbara region



For more information, please contact:

Corey Nolan Chief Executive Officer Phone: +61 (7) 3369 7058 Email: info@sayonamining.com.au

Sayona Mining Limited is an Australian, ASX-listed (SYA), company focused on sourcing and developing the raw materials required to construct lithium-ion batteries for use in the rapidly growing new and green technology sectors. Please visit us as at www.sayonamining.com.au

Competent Person Statement

The information in this report is based on information compiled by Mr. Simon Attwell, a Competent Person, and who is a Member of The Australasian Institute of Mining and Metallurgy. Mr. Attwell is an employee of Attgold Pty Ltd ("Attgold") which provides geological services to Sayona.

Mr. Attwell has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr. Attwell consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.



Rock Chip Assay Results

•	-				
SAMPLE	Easting	Northing	Li ₂ O %	Comment	Location
SP555459	610632	7671646	0.03	Green silicified pegmatite	North eastern pegmatite
SP555460	610637	7671630	0.03	Green silicified pegmatite	North eastern pegmatite
SP555461	610684	7671617	2.2	Spodumene pegmatite	North eastern pegmatite
SP555462	610685	7671618	0.87	Green silicified pegmatite	North eastern pegmatite
SP555463	610678	7671700	3.16	Spodumene pegmatite	North eastern pegmatite
SP555464	610363	7670125	2.86	Spodumene pegmatite	Main Eastern pegmatite
SP555465	610386	7669899	0.03	Green silicified pegmatite	Main Eastern pegmatite
SP555466	610355	7670151	3.98	Spodumene pegmatite, fresh	Main Eastern pegmatite
SP555467	610356	7670195	3.51	Coarse spodumene pegmatite	Main Eastern pegmatite
SP555468	610391	7670026	1.63	Spodumene pegmatite	Main Eastern pegmatite
SP555469	609431	7669989	0.52	Fine aplite with green muscovite	Western pegmatite
SP555470	609578	7670661	0.01	Simple pegmatite	Western pegmatite
SP555471	609441	7670565	0.02	Aplite	Western pegmatite
SP555472	610260	7670999	1.83	Spodumene pegmatite, quartz rich	Main Eastern pegmatite
SP555473	610267	7670950	1.99	Spodumene pegmatite, weathered and silicified	Main Eastern pegmatite
SP555474	610274	7671068	0.98	Silicified pegmatite with spodumene textures	Main Eastern pegmatite
SP555475	610267	7670842	0.01	Narrow pegmatite parallel to main body	Main Eastern pegmatite
SP555476	610277	7670848	0.01	Silicified aplite	Main Eastern pegmatite
SP555477	610288	7670816	0.74	Aplite with relict spodumene textures	Main Eastern pegmatite
SP555478	610341	7670397	2.73	Coarse spodumene pegmatite	Main Eastern pegmatite
SP555479	610343	7670378	0.07	Green silicified pegmatite	Main Eastern pegmatite
SP555480	610353	7670313	0.06	Green silicified pegmatite	Main Eastern pegmatite

Note: Datum is Australian Geodetic MGA Zone 50 (GDA94)

JORC Code, 2012 edition - Table 1 (section 1; Sampling Techniques and Data)

Criteria	JORC Code explanation	Commentary
Sampling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are 	 Geochemical samples have been collected as a first pass assessment and orientation of the project area. The samples have an irregular spacing reflecting the reconnaissance nature of the assessment. Samples are grab samples. The presence or absence of mineralisation was initially determined visually by the field geologist. The type of geochemical sampling is a standard approach during the initial style reconnaissance.



Criteria	JORC Code explanation	Commentary
	 Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. 	
Drilling techniques	• Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	Not applicable, no drilling has been carried out
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	Not applicable, no drilling has been carried out
Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	 Not applicable, no drilling has been carried out. This information is of insufficient detail to support any Mineral Resource Estimation.
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	 Not applicable, no drilling has been carried out No measures have been taken to ensure sampling is statistically representative of the in situ sampled material. The collection methodology is considered appropriate for this early stage assessment of the project. The sample size is considered appropriate to the early stage of exploration carried out.
<i>Quality of assay data and laboratory tests</i>	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. 	 Analysis was carried out by ALS, Brisbane which is a certified laboratory in compliance with AS/NZS- 9001:2000. Analysis, of a 48 element suite, was determined by mixed acid digest followed by ICP-MS61.



Criteria	JORC Code explanation	Commentary
	 For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	 Six samples which reported high Li values by this method were re-assayed by peroxide fusion, method ME-ICP89, to give a high precision result. This is considered a total digest appropriate to the samples submitted. Not used No additional quality control measures beyond that of the Laboratory QA/QC were implemented.
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	 The results are considered acceptable and have been reviewed by multiple geologists. The company conducts internal data verification protocols which have been followed. Li has been converted to Li₂O for the purposes of reporting. The conversion used was Li₂O = Li x 2.153. No other adjustments to assay data has been undertaken
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	 Samples were located during collection by handheld GPS The grid system used is Australian Geodetic MGA Zone 50 (GDA94). The level of topographic control offered by the handheld GPS is considered sufficient for the work undertaken
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	 There was no predetermined grid spacing to the rock sampling program. The data spacing and distribution is not sufficient to establish the degree of geological and grade continuity appropriate for Mineral Resource estimation procedures. Samples have not been composited.
<i>Orientation of data in relation to geological structure</i>	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	 Sampling was carried out over small areas of the project and it is not known if they are representative. Not applicable, no drilling has been carried out
Sample security	• The measures taken to ensure sample security.	 Industry standard sample collection and storage have been reported by the vendor geologist.
Audits or reviews	• The results of any audits or reviews of sampling techniques and data.	No audits or reviews of the data have been conducted at this stage



JORC Code, 2012 edition – Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	 The Mallina project, E47/2983 is part of a larger tenement portfolio held under Option Agreement with Great Sandy Pty Ltd. The Option terms and tenement details have been previously reported, for example in 21st December 2016 ASX release titled 'Option to Acquire New Pilbara Spodumene Discovery'. There are no impediments that have been identified for operating in the project areas
Exploration done by other parties	• Acknowledgment and appraisal of exploration by other parties.	 At Mallina past exploration has focused on the gold and base metal potential of the area. Together with government data provided by GSWA past information has allowed recognition of the projects potential.
Geology	• Deposit type, geological setting and style of mineralisation.	• Lithium is being targeted within rare metal pegmatites which represent the most fractionated and evolved pegmatite type. Sayona's main focus is in discovery of albite-spodumene pegmatite types which host high grade lithium mineralisation. Rare metal pegmatites are uncommon, typically hosted in greenstone rocks near to granite intrusion.
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	Drilling has not been carried out.
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	 No variation to laboratory reported assays has been made.



Criteria	JORC Code explanation	Commentary
Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	 Exploration is at an early stage and information contains insufficient data points to allow these relationships to be reported
Diagrams	 Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	Sample plans are attached
Balanced reporting	• Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.	All relevant assay results are reported herein.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	The exploration reported herein is at a very early stage but results are consistent with geological and other data
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale stepout drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 Further mapping and follow up sampling is required to define lithium targets and mineralisation for drill testing